

Pumps (Cat, Pratisoli & General Pumps)

- Industrial Heavy Duty Triplex Plunger Slow Speed Pumps
- Oil Bath Crankcase • Stainless Steel Valves • Manifold Available in Brass, Nickel, Aluminum, Bronze or 316 Stainless Steel • Belt Driven or Optional Gearbox Drive

Electric Motors

- 1750 RPM • TEFC • Full Frame • 1.25 Service Factors
- Thermo Overload Protection • Continuous Duty

Electrical Control Panel

- Nema 4 • Water Tight • Easy Access
- Auto Stop / Start With Time Delay

Frame

- All Welded • All Powder Coated • Super Heavy Duty Plate or Channel Iron Base Frame Assembled

Includes

- Liquid Filled SS Pressure Gauge • Adjustable Pressure Regulator

Options & Accessories

- Multi Pump and Multi Staging of Pumps • High Temp Shut Down • Pulsation Dampener • Pressure Blow Off • Tank Feed
- Steam/Hot Water Sensor Temp Controls • Level Controls
- Wash Station Foamers • Wash Station Control Systems
- Wash Station Valve Assemblies • VFD • PLC • Pressure Transducer

Designed for industrial and food processing plants that require 24 hour on demand cleaning capabilities throughout their operation. All requirements can be met no matter how large or small the need.



MODEL	GPM	PSI	HP	VOLTAGE
IP1010E-1	10	1000	7.5	208/440/575V 3ph
IP1510E-1	15	1000	10	208/440/575V 3ph
IP2110E-1	21	1000	15	208/440/575V 3ph
IP1022E-1	10	2200	15	208/440/575V 3ph
IP4210E-2	42	1000	2 x 15	208/440/575V 3ph
IP3612E-1	36	1200	30	208/440/575V 3ph
IP4510E-1	45	1000	30	208/440/575V 3ph
IP7212E-2	72	1200	2 x 30	208/440/575V 3ph
IP9010E-2	90	1000	2 x 30	208/440/575V 3ph
IP13510E-3	135	1000	3 x 30	208/440/575V 3ph
IP18010E-4	180	1000	4 x 30	208/440/575V 3ph
IP2320E-1	23	2000	30	208/440/575V 3ph
IP4620E-2	46	2000	2 x 30	208/440/575V 3ph
IP6012E-1	60	1200	50	208/440/575V 3ph
IP7010E-1	70	1000	50	208/440/575V 3ph
IP6010E-1	60	1000	40	208/440/575V 3ph
IP3025E-1	25	3000	50	208/440/575V 3ph
IP4020E-1	20	4000	50	208/440/575V 3ph